

Technical Information

TEGO® Antifoam 2–80

TEGO® Antifoam 2–80 is an antifoam emulsion based on organo-modified siloxanes.

Physical properties

Appearance	white emulsion
Active content	20 %
Density (20 °C) DIN 51757	approx. 1.0 g/cm ³
Viscosity , dynamic (25 °C) DIN 53019	approx. 150 mPas
pH-value (25 °C)	7 – 9, at delivered form

Application

TEGO® Antifoam 2–80 provides reliable foam control and excellent long-term efficiency especially in pressure sensitive adhesives. It may also be used in aqueous media, as well as in the processing and application of polymer dispersions, emulsions and a multitude of other industrial applications (e.g. industrial and household cleaners) where the use of traditional silicone oil based antifoams is restricted for certain reasons.

Benefits

The special raw material of TEGO® Antifoam 2–80 provides a unique product profile that combines excellent efficiency with maximum compatibility at the same time.

These properties cannot be achieved with organic or with traditional silicone oil based antifoams.

Furthermore undesirable effects associated with silicone based antifoams (silicone spotting, fish eyes) can be eliminated in most applications.

The TEGO® Antifoam product range exceeds customer requirements according to:

- Foam formation during compounding of a final formulation
- Foam formation during the application of the adhesive
- Inadequate storage stability


Dosage

In most applications it is beneficial to apply TEGO® Antifoam 2–80 pre-diluted in water (1 : 1 to 1 : 10).

Depending on the application in question the required dosage may vary over a wide range (0.05 – 0.2 %). Suitable screening tests are therefore recommended (initial dosage: 0.1 %).

Handling

Dilution of TEGO® Antifoam 2–80 may be prepared by adding the desired amount of water to TEGO® Antifoam 2–80 while stirring gently at low shear rates.



1 : 1 dilutions prepared as described above are stable for several days. 1 : 10 dilutions should be processed within several hours.

The product has to be stirred before use.

Food contact status

FDA regulation

TEGO® Antifoam 2–80 complies with 21 CFR 176.210 (Defoaming agents used in the manufacture of paper and paperboard) and 21 CFR 175.105 (Adhesives).

European Regulation 10/2011 and amendments

Detailed information is available on request.

Recommendations of the BfR

TEGO® Antifoam 2–80 complies with the XIVth BfR Recommendation.

Polymer dispersions that comply with the XIVth Recommendation may be further used as production auxiliary according to the BfR Recommendation XXXVI under B. I. 10.

Registration status

The components of TEGO® Antifoam 2–80 are listed in the following chemical inventories:

EINECS, TSCA, DSL, ENCS, AICS, ECL, PICCS, CHINA

Based on the submitted information of our raw material suppliers we can confirm, that TEGO® Antifoam 2–80 is compliant with EC Regulation 1907/2006 (REACH).

Storage stability

TEGO® Antifoam 2–80 is stable in closed containers for a minimum of 6 months. TEGO® Antifoam 2–80 must be stored in frost-free conditions.

Packaging

210 kg PE drums (840 kg each pallet)
1 000 kg containers

Hazardous goods classification

Information concerning

- classification and labelling according to regulations for transport and for dangerous substances
- protective measures for storage and handling
- measures in case of accidents and fire
- toxicity and ecological effects

is given in our material safety data sheets.

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.

Evonik Nutrition & Care GmbH
Goldschmidtstraße 100
45127 Essen, Germany
Phone Europe +49 201 173 2665
Phone Asia +86 21 61191 125
Phone Americas +1 804 727 0700
interface-performance@evonik.com
www.evonik.com/interface-performance

